

## **IMAGETEAM™ 4710LR/LX** *Fixed Mount 2D Image Reader*



### **Features**

*2D Image Reader - Hand held or fixed mount image reader for reading and decoding 2D symbologies, and capturing images.*

*Supports All Popular 2D Symbologies - Fixed mount IT4710 supports all popular matrix and stacked linear symbologies: MaxiCode, Aztec, Aztec Mesa, Data Matrix, PDF417, QR, and MicroPDF417.*

*Fixed Position Reader - Opens up new 2D bar code and image capture possibilities for fixed scanning applications.*

*Omni-Directional Scanning - CMOS-based video technology and image processing gives the IT4710 full omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.*

*Aiming - The IT4710 has a bright, intuitive, aiming line.*

*Autodiscriminates Between Supported Symbologies and Fonts - Reads all major linear, stacked linear, and matrix bar codes as well as machine readable fonts used in Optical Character Recognition (OCR).*

*2D Print Quality Assessment (PQA) - An easy and inexpensive approach to providing test results useful for 2D bar code symbol process control, and improvement of the overall 2D data acquisition system.*

The HHP IMAGETEAM™ (IT) 4710 Image Reader can be configured as either a hand held or fixed mount device that reads matrix, stacked linear, and conventional linear bar codes, as well as a single line of OCR-A and OCR-B fonts. Multi-line OCR applications can also be read. The IT4710 has the power to capture and download images to a PC for applications, such as signature capture, PC-based decoding, and image lift requirements.

The IT4710 Reader can be used in retail, packaging, transportation, printed circuit board manufacturing, electronic component manufacturing, and clinical/ diagnostic applications that include test tube and reagent package labels.

The IT4710 can be configured for keyboard wedge, Non Decoded Output (Code 128 emulation), TTL, or True RS-232. The IT4710 connects to all popular PCs and portable data terminals. The Non Decoded Output mode can be used with external wedge decoders and portable terminals or other devices without 2D decoding capability.

The IT4710 features integrated processing for a one-piece scanning solution -- no additional boxes or electronics needed. The reader provides omni-directional and auto-discrimination decoding for symbologies, such as MaxiCode, PDF417, QR, Data Matrix, Aztec code, RSS code, composite codes, postal codes, Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, UPC, and EAN. Additional symbologies will be added based on market demand.

Because the IT4710 is a fixed focus device, four product models with different focal points are available. The IT4710LX, designed for reading wide codes at up to 15 inches on PDF, has a focal point of 7 inches from the nose. It is ideal for reading the 1D and 2D labels found in the transportation industry. The IT4710LR, designed for low and medium density codes, has a focal point of 5 inches from the nose. It is ideal for general 2D applications (postal, retail, and asset tracking). The high density (HD) models of the IT4710 are highlighted in a separate data sheet.

To learn how the IT4710 can work for you, contact us at any of the locations listed on the back or visit us at [www.hhp.com](http://www.hhp.com).

**Upgrade your image.**



# IMAGETEAM™ 4710LR/LX Specifications

## Performance

**LX Focal Point:** 7 inches from nose  
**LR Focal Point:** 5 inches from nose

<b>LX Working Range:</b> (typical)	<b>12 pt OCR-A</b> <b>12 cpi</b>	<b>10 mil Linear</b> <b>(.025 cm)</b>	<b>13 mil UPC</b> <b>(.033 cm)</b>	<b>15 mil Data Matrix</b> <b>(.038 cm)</b>	<b>6.6 mil PDF</b> <b>(.017 cm)</b>	<b>10 mil PDF</b> <b>(.038 cm)</b>
<b>Near</b>	1.6 in. (4.1 cm)	2.1 in. (5.3 cm)	2.3 in. (5.8 cm)	3.7 in. (9.4 cm)	4 in. (10.2 cm)	2.7 in. (6.9 cm)
<b>Far</b>	12.3 in. (31.2 cm)	9.5 in. (24.1 cm)	13 in. (33 cm)	5.9 in. (15 cm)	6.3 in. (16 cm)	9.8 in. (24.9 cm)
<b>LR Working Range:</b>	<b>12 pt OCR</b> <b>12 cpi</b>	<b>5 mil Linear</b> <b>(.013 cm)</b>	<b>13 mil Linear</b> <b>(.033 cm)</b>	<b>15 mil Data Matrix</b> <b>(.038 cm)</b>	<b>6.6 mil PDF</b> <b>(.017 cm)</b>	<b>10 mil PDF</b> <b>(.025 cm)</b>
<b>Near</b>	1.9 in. (4.8 cm)	3 in. (7.6 cm)	1.9 in. (4.8 cm)	2 in. (5.1 cm)	2.7 in. (6.9 cm)	2.4 in. (6.1 cm)
<b>Far</b>	8.7 in. (22.1 cm)	4.3 in. (10.9 cm)	9.4 in. (23.9 cm)	5.8 in. (14.7 cm)	5.2 in. (13.2 cm)	7.7 in. (19.6 cm)

**Rotational Sensitivity:** 360°  
**Viewing Angle:** ±45°  
**Ambient Light:** Total darkness to 100,000 lux (full sunlight)  
**Aiming:** 660nm LEDs provide bright aiming line

## Symbologies

**2 Dimensional:** MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake\*, Vericode\*, Dataglyphs\*  
**Linear:** Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS, BC 412\*, Code 93, Codablock\* available to licensed users only  
**Postal:** Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code  
**OCR Fonts:** OCR-A, OCR-B  
**Interfaces:** RS232, Wedge, and HHLC (Code 128 Emulation)  
**Programmable Options:** Baud, Parity, Data Formatting, Code Options

## Mechanical/Electrical

**Dimensions**  
**Length:** 4.85 in. (12.3 cm)  
**Height:** 1.85 in. (4.7 cm)  
**Width:** 2.50 in. (6.4 cm)  
**Weight w/o cord:** 5.5 oz. (156 g) or less  
**Power Requirements:** 4 to 9 volts  
**Current Draw:** Low Power Mode - average @ 5VDC - 40mA  
 Medium Power Mode - average @ 5VDC - 125mA  
 High Power Mode - average @ 5VDC - 175mA  
**Standby Current:** < 200µA @ 5V

## Environmental

**Temperature**  
**Operating:** -0°C to 50°C  
**Storage:** -40°C to +70°C  
**Humidity:** 95% RH, non condensing at 50°C  
**Shock:** 10 drops 5 ft. to concrete @ room temperature  
**ESD:** Functional after 15KV discharge  
**Agency:** FCC Class B, CE

**CE** Complies with EMC 89/336/EEC and LVD 73/23/EEC

## Worldwide Offices

**Offices Serving North America**  
 Skaneateles Falls, NY  
 Tel: +1 315 685 8945  
 or, in North America: +1 800 782 4263  
 sales@hhp.com  
 Charlotte, NC  
 Tel: +1 704 998 3998  
 or, in North America: +1 800 782 4263  
 sales@hhp.com

**Offices Serving Europe, Middle East, and Africa**  
 Europe  
 Tel: +31 (0) 40 29 01 600  
 euro\_sales@hhp.com  
 United Kingdom  
 Tel: +44 (0) 1 925 240055  
 euro\_sales@hhp.com  
 Ireland  
 Tel: +353 (0) 502 44007  
 euro\_sales@hhp.com

**France**  
 Tel: +33 (0) 1 461 04111  
 euro\_sales@hhp.com  
**Germany**  
 Tel: +49 (0) 7 477 151377  
 euro\_sales@hhp.com  
**Spain**  
 Tel: +34 93 228 76 68  
 euro\_sales@hhp.com

**Offices Serving Asia and the Pacific Rim**  
**Hong Kong**  
 Tel: +852 2511 3050/2511 3132  
 asia\_sales@hhp.com  
**Japan**  
 Tel: +813 52127392  
 asia\_sales@hhp.com

**Offices Serving Latin America**  
**Naples, Florida**  
 Tel: +1 239 263 7600  
 la-sales@hhp.com  
**São Paulo**  
 Tel: +55 11 5016 3454  
 la-sales@hhp.com  
**Rio De Janiero**  
 Tel: +55 21 2494 7060  
 la-sales@hhp.com

Web Site Address [www.hhp.com](http://www.hhp.com)  
 Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2002. All rights reserved. Printed in the U.S.A.  
 Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.