



Powerful Intel[®] XScale[™] processor

Product

Profile

- Microsoft[®] Windows[®] Mobile software for Pocket PC provides compatibility, enterprise features
- Built-in wireless LAN and Bluetooth[™] connectivity for communication without wires
- Advanced linear imaging technology to read barcodes quickly and reliably
- Bright color display provides easy readability under all lighting conditions
- Ergonomically designed for comfortable full-day use
- Part of a comprehensive solution including printers, application software, communications infrastructure products, peripherals, and accessories

730 COLOR MOBILE COMPUTER

With its compact form factor and rich feature set, the Intermec[®] 730 color mobile computer is ideally suited for a variety of data collection tasks. Building on the standards set by the highly-flexible and configurable 700 Color Series, the 730 delivers a targeted set of features at a very attractive price.

The 730 extends the successful 700 Color Series, providing a compact, durable unit equipped with local area and personal area wireless radios, as well as a revolutionary linear imager that delivers high-speed barcode reading performance. Ideally suited for in-premise environments, the 730 is also equipped to handle the rigors of outdoor use. The 730 provides a sharp color display that is easy to read in all lighting conditions, including sunlight. The numeric keypad and touch screen facilitate data entry.

Like all Intermec mobile computers, the 730 is a fully integrated system. The radios and imager are incorporated into the basic product design, ensuring maximum performance and years of troublefree service.

The 730 is tested to the exacting standards of the Intermec Reliability Labs to provide you with a system tough enough to handle the daily rigors of your frontline business.

Whether your application is standalone, client-server, browserbased, or terminal emulation, the 730 is the right tool for the job. V

 Physical Characteristics

 Length: 178 mm (7.0 in.)

 Width: 89 mm (3.5 in.)

 Height: 38 mm (1.5 in.)

 Weight: 420 grams (15 oz)

Environmental

Operating Temp: -10° to +55°C (+14° to +131°F) Storage Temp: -20° to +60°C (-4° to +140°F) Relative Humidity: 5% to 95% (non-condensing) Rain and Dust Resistance: IP54 compliant Drop Spec: Withstands 1.2m (4') drop, 26 times onto concrete

Power

Battery Type: Lithium-Ion, 3.6V, (1 x 2400 mAh cell), customer replaceable Battery Capacity: 8.64 Watt-hours Battery Life: 6-10 hours, application dependent Recharging Time: 4 hours

Microprocessor

Intel[®] XScale[™] PXA255 Applications Processor, 400 MHz

Operating System

Microsoft[®] Windows[®] Mobile software for Pocket PC Memory and Storage RAM Memory: 64 MB Flash ROM: 64 MB; includes ROM folder for application storage

Expansion Slot Secure Digital (SD)

Display

Transflective TFT all-light readable color display with LED backlight, 240x320 pixels, 89mm (3.5 in) diagonal, 64 K colors

Standard Communications RS232, USB, IrDA 1.1 (115 kbps)

Integrated Wireless 802.11b WLAN (Wi-Fi® certified) Bluetooth™* compatible module

Integrated Scanner Options Linear imager

Cisco Compatible Extensions Version 1 Supported LEAP CKIP VLAN

Regulatory Approvals FCC Part 15 Class B

UL Listing CE Mark CB Report

Imager Specifications

Density	Minimum	Maximum
4 mil	3.7 in.	5.4 in.
(0.1mm)	(95 mm)	(136 mm)
12 mil	1.8 in.	9.4 in.
(0.3mm)	(45 mm)	(240 mm)
20 mil	1.7 in.	11.8 in.
(0.5mm)	(44 mm)	(300 mm)
39 mil	4.7 in.	15.7 in.
(1mm)	(120 mm)	(400 mm)
100% UPC	1.8 in.	9.4 in.
	(45 mm)	(240 mm)
25% UPC	2.4 in.	6.2 in.
	(61 mm)	(157 mm)

Key Accessories

Portable and vehicle-mounted printers Vehicle dock Desktop connectivity dock Desktop dock with integrated modem Charge-only Multidock Battery pack chargers Scanning handles

* Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

Microsoft, Windows, the Windows logo, Windows Media, Outlook, and ActiveSync are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Intel- and XScale- are trademarks of Intel Corporation.

North America Corporate Headquarters 6001 36th Avenue West

6001 36th Avenue West Everett, Washington 98203 tel: 425.348.2600 fax: 425.355.9551

Systems & Solutions 550 2nd Street S.E. Cedar Rapids, Iowa 52401 tel: 319.369.3100 fax: 319.369.3453

Media Supplies 9290 Le Saint Drive Fairfield, Ohio 45014 tel: 513.874.5882 fax: 513.874.8487

Canada

7065 Tranmere Drive Mississauga, Ontario L55 1M2 Canada tel: 905.673.9333 fax: 905.673.3974

Europe/ Middle East & Africa Headquarters Sovereign House Vastern Road

Reading RG1 8BT United Kingdom tel: 44.118.987.9400 fax: 44.118.987.9401

Asia Asia Regional Office 25-16 International Plaza 10 Anson Road Singapore 079903 tel: 65.6324.8391 fax: 65.6324.8393

Australia

Level 7, 200 Pacific Highway Crows Nest, NSW 2065 Australia tel: 61.2.9492.4400 fax: 61.2.9954.6300 South America & Mexico Latin America Headquarters 17921 B Skypark Circle Irvine, California 92614 tel: 949.442.9393 fax: 949.757.1687

Intermec South America Ltda. Rua Arandu 1544-15 andar Edificio Itavera Brooklin Novo 04562-031 Sao Paulo, SP Brazil tei: 55.11.5501.2070

Mexico Tamulipas 141, Primero Piso 06140 Mexico, D.F. tel: 525.55.211.1919 fax: 525.55.211.8121 Worldwide Fax Document Retrieval Service 800.755.5505 (North America Only) tel: 650.556.8447

Internet www.intermec.com

Sales 800.347.2636 (toll free in N.A.) tel: 425.348.2726

Service and Support 800.755.5505 (toll free in N.A.) tel: 425.356.1799 Copyright © 2004 Intermec Technologies Corporation. All rights reserved. Interme is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611467-018 03/04

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.