

Product Profile

- PDA form factor built to withstand the rigors of field use
- Delivers improved TCO over commercial grade devices
- Features and functionality common to higher priced, larger mobile devices
- Choices of radios, keypads and platforms to fit the job at hand
- SmartSystem™ device management capabilities for batch or real-time updates and maintenance



CN2 MOBILE COMPUTER FAMILY (CN2A & CN2B)

The powerful CN2 family, including the CN2A and CN2B, combines the convenience of shirt pocket size for the ultimate in mobility, with all the ruggedness and reliability you've come to expect from Intermec, the number one supplier of rugged pocket PCs for the enterprise.¹

While the CN2A, with either batch or local area radio connectivity, is ideally suited for Store Operations/ Management applications within the Retail industry, the CN2B offers the addition of Microsoft® Windows Mobile and Bluetooth support, a good fit for Field Service, Direct Store Delivery, or In-Transit Visibility applications that can run in near-real-time by connecting to a mobile phone when integrated WWAN capabilities are not required.

While the CN2 family shares the compact form factor of a commercial PDA, including single-handed operation, the similarities stop there. The thoughtfully designed feature set is packaged to survive heat, humidity and multiple drops to concrete or steel, allowing you to minimize your total cost of ownership. Research has proven that investments in rugged mobile computing devices versus commercial grade pay off in a lower total cost of ownership as early as two years into the life of the device².

Device management capabilities are uncommon for this class of mobile computer; however both the CN2A and CN2B have integrated Intermec's SmartSystems™, a centralized one-to-one device management solution for remote

support capability. The CN2 family also features Wavelink Avalanche™ for remote maintenance of entire populations of devices. Both solutions allow the user to configure, update or maintain the CN2 mobile computers in real time or batch saving time and money.

This mobile computer family relies on the proven, powerful combination of the Intel® XScale™ processor with either the Microsoft® Windows CE or Windows Mobile operating system to deliver a perfect balance of real-time data collection performance with full-shift power management functionality required by the application demands of retail store management and field sales and service.

In addition, the CN2 family relies on Intermec's WiFi® certified 802.11 b/g radio, which ensures consistent performance by providing the best available wireless network throughput and reliability.

Both the CN2A and CN2B leverage the Intermec® EV10 linear scan engine with 3.3V low power operation to preserve battery life for mobile computing applications. With no moving parts and no laser diode, the EV10 has a longer life than any laser scanner (MTBF above 250Kh). Both the CN2A and CN2B have received Cisco Certified Extension (CCX) ensuring compatibility with a Cisco infrastructure.

The user accessible secure digital card slot provides more than sufficient data storage and back up capabilities for today's demanding applications.

¹ Venture Development Corporation (VDC); Intermec ranked #1 for 2004 Global Rugged Computer Market

² TCO Models for Mobile Computing and Communications Platforms, VDC, Dec. 2003

Physical Description

The CN2 family are rugged pen based handheld mobile data collection computers featuring an embedded Microsoft® Windows® operating system and an Intel™ XScale™ PXA255 processor. The shirt pocket, PDA-like form factor, integrated linear imager and choice of radios make the CN2 family the ideal computers for the mobile worker. Although they share the same casing, the CN2A and CN2B are based on different architecture. Reference the following product specifications common to both the CN2A and CN2B as well as the product differentiation chart to determine the device that best meets your application requirements.

Physical Characteristics

Length: 147 mm (5.8 in.)
Height: 35 mm (1.4 in.)
Width: 86 mm (3.4 in.)
Weight: 370 grams (11.9 oz)

Hardware

Microprocessor: Intel XScale PXA255; 400 MHz
Display: 240 x 320 (1/4 VGA) transfective display with 3.5" diagonal supporting 16-bit color depth (65K colors) and resistive panel touch screen. Integrated stylus storage slot.

Software

Development Environments: Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET and C#)
Browser Support: IE6 compatible
Software Development Kit: Supports device-specific features and bar code scanning
Bundled Productivity Applications: WordPad, Transcriber and Imager scan demo program

Scan Activation

Left/Right/Top scan buttons, with continuous scan mode.

Integrated radio

Data Rates: Up to 54 Mbps with 802.11g; 11 Mbps with 802.11b
Antenna: Internal
Standards Compliant: IEEE 802.11g (2.4 GHz - OFDM), IEEE 802.11b (2.4 GHz - DSSS)
Radio Power: 802.11g 16mW. 802.11b 30mW
Security: WEP, WPA, WPA 2, EAP-FAST, 802.1x (EAP-TLS, TTLS, LEAP, PEAP)
Certifications: Wi-Fi, WPA, Cisco Compatible logo indicates compatibility with a Cisco infrastructure

Device Management

SmartSystem™ Support: A centralized one-to-one device management solution for remote support capability. Also features Wavelink Avalanche™ for

remote maintenance of entire populations of devices. Both solutions allow the user to configure, update or maintain the CN2 mobile computers in real time or batch.

Speaker

Loud (80 dB) programmable "beeper" with adjustable frequency and duration for scanning feedback or audio indicator under program control. The CN2B features an audio jack.

Power

Battery Type: Lithium-Ion 2150 mAh, 3.7V with 5 min. NiMH RAM backup
Battery Life: 8 or more hours at typical usage level
Recharging Cycle: 4 hours

Environmental Specifications

Humidity: 5 to 95% non-condensing
Electrostatic Discharge: 6KV contact, 12KV air
Vibration and Shock Protection: Tested to MIL-PRF-28800F standards

Accessories

I/O Interface: USB version 1.1 (through dock)
Serial Adapters: Snap-on for DB9 interface to serial or printer peripherals (externally powered)

Regulatory Approvals

UL and cUL Listed, GS Licensed, FCC Part 15, Industry Canada ICES-003 and RSS-210, Australia C-Tick, CE Mark, Japan Telec



Product Differentiation Chart

	CN2A	CN2B
Operating System	Microsoft WinCE 4.2	Windows Mobile 2003
Memory Capacity	• 128 MB RAM/64 MB Flash	• 64 MB/64 MB
Wireless Technologies	• 802.11 b/g or Batch option	• 802.11 b/g and Bluetooth™
Keypad Options	• Navigation • 18 key numeric	• 22 key numeric
Bar Code Scanning	• Integrated 1D Linear Imager or scannerless option • Symbologies: Codabar; Code 39; Code 128; Interleaved 2 of 5, and limited forms of UPC and EAN.	• Integrated 1D Linear Imager • Symbologies: Codabar; Codablock A and F; Code 11; Code 39; Code 93 and 93i; Code 128; EAN 128; I 2 of 5; ISBT 128; MSI; Matrix 2 of 5; Plessey; RSS 14; RSS Limited; RSS Expanded; RSS 14 Stacked; RSS Omni-Directional; Standard 2 of 5; Telepen; UPC/EAN; UCC Composite CC-A, CC-B and CC-C; Micro PDF and PDF 417.
Environmental Specifications	• IP64, 26 drops from .91m (3 ft.) to steel or concrete Operating temp: 0 to 50° C (32° to 122°F) Storage temp: -10° to 50° C (14° to 122°F)	• IP54, 1.22m (4 ft.) drops to concrete using MIL standard 810F Operating temp: -10° to 50° C (14° to 122° F) Storage temp: -20° to 60° C (-4° to 140°F)
Accessories Supported	• Single USB client dock • Single USB modem dock* • Ethernet dock** • Vehicle dock** • AC wall adapter • Car charger** • Quad battery-pack charger** Dust cover, holster, spare battery, hand strap, stylus kit, screen protector kit.	• Single USB client dock • Single USB modem dock* • Vehicle dock** • AC wall adapter • Car charger** • Quad battery-pack charger** Dust cover, holster, spare battery, hand strap, stylus kit, screen protector kit.

* This dock supports USB client, modem and host for the CN2A; and USB client and modem only for the CN2B.

** Indicates Accessories that are planned but have not been released to the market

North America

Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada
 7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

Europe/ Middle East & Africa

Headquarters
 Reading International Business Park
 Basingstoke Road
 Reading RG2 6DD
 United Kingdom
 tel: 44.118.923.0800
 fax: 44.118.923.0801

Asia
Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office
 29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86.10.5165.5922
 Fax: 86.10.6567.6778

Australia

Level 4, 1-3 Atchison Street
 St. Leonards, NSW 2065
 Australia
 tel: 61.2.9330.4400
 fax: 61.2.9437.0204

South America & Mexico
Intermec South America Ltda.
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico
 Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.241.4800
 fax: 525.55.211.8121

Internet

www.intermec.com

Sales
 800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611570-02D 11/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

